



TECHNICAL DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 12.05.2021

Revision: 15.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** For Industrial, professional and consumer only
- **Trade name:** Thinner 2661
- **Article number:** 2661
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture**
Surface Coating
Surface Coating
Thinner
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
HMG PAINTS LIMITED
Riverside Works,
Collyhurst Road,
Collyhurst,
Manchester,
M40 7RU
UNITED KINGDOM
TEL: +44 (0)161 205 7631
EMAIL: sales@hmgpaint.com
- **Further information obtainable from:** sales@hmgpaint.com
- **1.4 Emergency telephone number:** +44 (0)161 205 7631 (business hours)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2	H225	Highly flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Dam. 1	H318	Causes serious eye damage.
Repr. 2	H361d	Suspected of damaging the unborn child.
STOT SE 3	H336	May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

- **Signal word** Danger

(Contd. on page 2)

GB

Trade name: Thinner 2661

(Contd. of page 1)

· Hazard-determining components of labelling:

Toluene
cyclohexanone
Xylene (mix)
ethylbenzene

· Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H361d Suspected of damaging the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards
· Results of PBT and vPvB assessment
· PBT:

108-88-3	Toluene
----------	---------

· vPvB:

108-88-3	Toluene
----------	---------

SECTION 3: Composition/information on ingredients
· 3.2 Chemical characterisation: Mixtures
· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-xxxx	Toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 3, H412 PBT; vPvB	>50-≤100%
CAS: 108-94-1 EINECS: 203-631-1 Reg.nr.: 01-2119453616-35-XXXX	cyclohexanone ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	>10-≤25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	Butyl ethanoate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	>2.5-≤10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	methyl ethyl ketone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	>2.5-≤10%

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Printing date 12.05.2021

Revision: 15.02.2021

Trade name: Thinner 2661

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	propan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	(Contd. of page 2) >2.5-≤10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	Xylene (mix) ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	>2.5-≤10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.
Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB

Trade name: Thinner 2661

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 Keep receptacles tightly sealed.
 Ensure good ventilation/extraction at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Hygiene measures:
 Wash hands before breaks and at the end of workday.
- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
Storage:
 · **Requirements to be met by storerooms and receptacles:** Store in a cool location.
 · **Information about storage in one common storage facility:** Not required.
 · **Further information about storage conditions:**
 Keep receptacle tightly sealed and in a well-ventilated place.
 Keep away from heat.
 Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

 · **Ingredients with limit values that require monitoring at the workplace:**
108-88-3 Toluene

WEL	Short-term value: 384 mg/m ³ , 100 ppm
	Long-term value: 191 mg/m ³ , 50 ppm
	Sk

108-94-1 cyclohexanone

WEL	Short-term value: 82 mg/m ³ , 20 ppm
	Long-term value: 41 mg/m ³ , 10 ppm
	Sk, BMGV

123-86-4 Butyl ethanoate

WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm

78-93-3 methyl ethyl ketone

WEL	Short-term value: 899 mg/m ³ , 300 ppm
	Long-term value: 600 mg/m ³ , 200 ppm
	Sk, BMGV

67-64-1 propan-2-one

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm

1330-20-7 Xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

(Contd. on page 5)

GB

according to 1907/2006/EC, Article 31

Printing date 12.05.2021

Revision: 15.02.2021

Trade name: Thinner 2661

(Contd. of page 4)

· DNELs		
108-88-3 Toluene		
Oral	DNEL	8.13 mg/day (Con)
Dermal	DNEL	226 mg/day (Con)
		384 mg/day (Ind)
Inhalative	DNEL	56.5 mg/m ³ (Con)
		192 mg/m ³ (Ind)
108-94-1 cyclohexanone		
Dermal	DNEL	4 mg/day (Ind)
Inhalative	DNEL	40 mg/m ³ (Ind)
123-86-4 Butyl ethanoate		
Oral	DNEL	2 mg/day (Con)
Dermal	DNEL	6 mg/day (Con)
		11 mg/day (Ind)
Inhalative	DNEL	35.7 mg/m ³ (Con)
		300 mg/m ³ (Ind)
78-93-3 methyl ethyl ketone		
Oral	DNEL	31 mg/day (Con)
Dermal	DNEL	412 mg/day (Con)
		1,161 mg/day (Ind)
Inhalative	DNEL	106 mg/m ³ (Con)
		600 mg/m ³ (Ind)
67-64-1 propan-2-one		
Oral	DNEL	62 mg/day (Con)
Dermal	DNEL	62 mg/day (Con)
		186 mg/day (Ind)
Inhalative	DNEL	200 mg/m ³ (Con)
		1,210 mg/m ³ (Ind)
1330-20-7 Xylene (mix)		
Dermal	DNEL	108 mg/day (Con)
		180 mg/day (Ind)
Inhalative	DNEL	14.8 mg/m ³ (Con)
		77 mg/m ³ (Ind)

· PNECs

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

CAS No. 123-86-4 Butyl Acetate

- Freshwater: 0.18 mg/l
- Marine water: 0.018 mg/l
- Fresh water sediment: 0.981 mg/kg
- Marine sediment: 0.0981 mg/kg
- Soil: 0.0903 mg/kg
- STP (sewage-treatment plant): 35.6 mg/l
- Intermittent use/release: 0.36 mg/l

(Contd. on page 6)

GB

according to 1907/2006/EC, Article 31

Printing date 12.05.2021

Revision: 15.02.2021

Trade name: Thinner 2661

(Contd. of page 5)

· Ingredients with biological limit values:

108-94-1 cyclohexanone

BMGV 2 mmol/mol creatinine
 Medium: urine
 Sampling time: post shift
 Parameter: cyclohexanol

78-93-3 methyl ethyl ketone

BMGV 70 µmol/L
 Medium: urine
 Sampling time: post shift
 Parameter: butan-2-one

1330-20-7 Xylene (mix)

BMGV 650 mmol/mol creatinine
 Medium: urine
 Sampling time: post shift
 Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

· **Respiratory protection:** When spraying the product, use a respiratory protective device.

· **Protection of hands:**

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.

(Contd. on page 7)

GB

Trade name: Thinner 2661

(Contd. of page 7)

108-94-1 cyclohexanone		
Oral	LD50	1,620 mg/kg (rat)
Dermal	LD50	764 mg/kg (rat)
Inhalative	LC50/4 h	6.2 mg/l (rat)
123-86-4 Butyl ethanoate		
Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	14,112 mg/kg (Rab)
Inhalative	LC50/4 h	23.4 mg/l (Rat)
78-93-3 methyl ethyl ketone		
Oral	LD50	3,460 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rab)
67-64-1 propan-2-one		
Oral	LD50	5,800 mg/kg (Rat)
Dermal	LD50	15,800 mg/kg (Rat)
Inhalative	LC50/4 h	76 mg/l (Rat)
1330-20-7 Xylene (mix)		
Oral	LD50	5,000 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	11 mg/l (Rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
- Acute Fish toxicity
n-Butyl acetate
LC50 18 mg/l
Species: *Pimephales promelas* (fathead minnow)
Exposure duration: 96 h
- Chronic Fish toxicity
n-Butyl acetate
No data available.
- Acute toxicity for daphnia
n-Butyl acetate
EC50 44 mg/l

(Contd. on page 9)

Trade name: Thinner 2661

(Contd. of page 8)

Species: Daphnia (water flea)
Exposure duration: 48 h

Chronic toxicity to daphnia
n-Butyl acetate
NOEC 23 mg/l

Species: Daphnia magna (Water flea)
Exposure duration: 21 d
Method: OECD Test Guideline 211

Acute toxicity for algae
n-Butyl acetate
EC50 675 mg/l
Species: Scenedesmus quadricauda (Green algae)
Exposure duration: 72 h

Acute bacterial toxicity
EC50 356 mg/l
Species: activated sludge
Exposure duration: 40 h

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

108-88-3	Toluene
----------	---------

· **vPvB:**

108-88-3	Toluene
----------	---------

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**

· **ADR**


1263 PAINT RELATED MATERIAL (vapour pressure at 50°C not more than 110 kPa)

(Contd. on page 10)

GB

Trade name: Thinner 2661

(Contd. of page 9)

· IMDG, IATA	<i>PAINT RELATED MATERIAL</i>
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	<i>3 Flammable liquids.</i>
· Label	<i>3</i>
· 14.4 Packing group	
· ADR, IMDG, IATA	
<i>II</i>	
· 14.5 Environmental hazards:	
· Marine pollutant:	
<i>No</i>	
· 14.6 Special precautions for user	
<i>Warning: Flammable liquids.</i>	
· Hazard identification number (Kemler code):	
<i>33</i>	
· EMS Number:	
<i>F-E,S-E</i>	
· Stowage Category	
<i>B</i>	
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	
<i>Not applicable.</i>	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	<i>5L</i>
· Excepted quantities (EQ)	<i>Code: E2</i>
	<i>Maximum net quantity per inner packaging: 30 ml</i>
	<i>Maximum net quantity per outer packaging: 500 ml</i>
· Transport category	<i>2</i>
· Tunnel restriction code	<i>D/E</i>
· IMDG	
· Limited quantities (LQ)	<i>5L</i>
· Excepted quantities (EQ)	<i>Code: E2</i>
	<i>Maximum net quantity per inner packaging: 30 ml</i>
	<i>Maximum net quantity per outer packaging: 500 ml</i>
· UN "Model Regulation":	<i>UN 1263 PAINT RELATED MATERIAL (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II</i>

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- *Directive 2012/18/EU*
- *Named dangerous substances - ANNEX I None of the ingredients is listed.*
- *Seveso category P5c FLAMMABLE LIQUIDS*
- *Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t*
- *Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t*
- *REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48*

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	100.0

(Contd. on page 11)

GB

Trade name: Thinner 2661

(Contd. of page 10)

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Full text of H-Statements referred to under sections 2 and 3:**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department: LABORATORY

· **Contact:** Health & Safety Officer

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity - oral – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB